



**WOOD TABLES** 

## Standard "H" Frame Table



	Without [		With Drawers				
Width	Standing Hgt.	Sitting Hgt.	# Drws	Standing Hgt.	Sitting Hgt.		
24"	TAC1124W	TAC2124W	1	TAA1124W	TAA2124W		
30"	TAC1130W	TAC2130W	1	TAA1130W	TAA2130W		
36"	TAC1136W	TAC2136W	1	TAA1136W	TAA2136W		
42"	TAC1142W	TAC2142W	1	TAA1142W	TAA2142W		
48"	TAC1148W	TAC2148W	2	TAB1148W	TAB2148W		
60"	TAC1160W	TAC2160W	2	TAB1160W	TAB2160W		
72"	TAC1172W	TAC2172W	2	TAB1172W	TAB2172W		
1000mm	TAC110BW	TAC210BW	1	TAA110BW	TAA210BW		
1500mm	TAC110CW	TAC210CW	2	TAB110CW	TAB210CW		

QUALITY BY DESIGN

• When ordering a table with drawers to match Architectural Overlay design use option code "OLP" to add flush overlay panel.

# Six Leg Combination Table



	Without D	With Drawers			
Width	Standing Hgt.	Sitting Hgt.	# Drws	Sitting Hgt.	
72"	TCC1172W	TCC2172W	2	TCB1172W	TCB2172W
84"	TCC1184W	TCC2184W	2	TCB1184W	TCB2184W
96"	TCC1196W	TCC2196W	4	TCB1196W	TCB2196W
2000mm	TCC110DW	TCC210DW	2	TCB110DW	TCB210DW

• When ordering a table with drawers to match Architectural Overlay design use option code "OLP" to add flush overlay panel.

**WOOD TABLES** 

# Standard "H" Frame Table



	Without [	With Drawers			
Width	Standing Hgt.	Sitting Hgt.	# Drws	Standing Hgt.	Sitting Hgt.
24"	TAC1224W	TAC2224W	1	TAA1224W	TAA2224W
30"	TAC1230W	TAC2230W	1	TAA1230W	TAA2230W
36"	TAC1236W	TAC2236W	1	TAA1236W	TAA2236W
42"	TAC1242W	TAC2242W	1	TAA1242W	TAA2242W
48"	TAC1248W	TAC2248W	2	TAB1248W	TAB2248W
60"	TAC1260W	TAC2260W	2	TAB1260W	TAB2260W
72"	TAC1272W	TAC2272W	2	TAB1272W	TAB2272W
1000mm	TAC120BW	TAC220BW	1	TAA120BW	TAA220BW
1500mm	TAC120CW	TAC220CW	2	TAB120CW	TAB220CW

• When ordering a table with drawers to match Architectural Overlay design use option code "OLP" to add flush overlay panel.

# Six Leg Combination Table



	Without D	With Drawers				
Width	Standing Hgt.	Sitting Hgt. # Drws		Standing Hgt.	Sitting Hgt.	
72"	TCC1272W	TCC2272W	2	TCB1272W	TCB2272W	
84"	TCC1284W	TCC2284W	2	TCB1284W	TCB2284W	
96"	TCC1296W	TCC2296W	4	TCE1296W	TCE2296W	
2000mm	TCC120DW	TCC220DW	2	TCE120DW	TCE220DW	

• When ordering a table with drawers to match Architectural Overlay design use option code "OLP" to add flush overlay panel.





QUALITY BY DESIGN

## **WOOD TABLES**

#### Hybrid Wood Table With Welded Steel Frame



Width	22" Deep	28" Deep	
48"	TAH2148	TAH2248	
60"	TAH2160	TAH2260	
72"	TAH2172	TAH2272	

- · Heavy-duty steel apron is clad with your choice of veneer and is designed to support 1000 lbs.
- . 2-1/2"  $\times$  2-1/2" wood legs with telescoping stainless steel inserts that are height-adjustable from 28-3/4" to 38-3/4" high. Legs are pin adjustable in 1"
- The table has 7" modesty rails on three sides with a 2" front rail.
- . Ships partially assembled.

## STEEL TABLES

#### Vibration Isolation Table



	Typical Non-l For 2			nick Work S eep Tables	urface	<b>;</b>	
<b>Q</b> _					18	3.5"	24" or 30"
		<u> </u>	3.5″—				
		38", 4	4", 50"		_		

	22″ 🛭	Реер	28" Deep			
Width	Standing Hgt.	Standing Hgt. Sitting Hgt.		Sitting Hgt.		
36"	VIT1136	VIT2136	VIT1236	VIT2236		
42"	VIT1142	VIT2142	VIT1242	VIT2242		
48"	VIT1148	VIT2148	VIT1248	VIT2248		

The Vibration Isolation Table is designed to provide stable working conditions for devices that are sensitive to vibration and shocks. Table consists of an outer table frame that supports the main work surface which is not isolated from vibration and an inner table frame that is entirely separate and supports the inner isolated work surface. This ensures vibrations are not transmitted to the isolated inner work surface.

- Outer Table Frame consists of two 18 gauge hollow vertical pedestals. Each pedestal has removable inner panels for access the anchor bolts and levelers. Pedestals are connected with 16 gauge steel rails. A flange is provided around the perimeter of the pedestals for mounting of the non-isolated work surface.
- Inner Table Frame consists of a rectangular hollow steel welded frame with each leg supplied with levelers and provisions for anchoring. Legs are joined by 11 gauge steel angles which support the isolated platform.
- Isolated Platform consists of a formed 18 gauge steel tray that is to be filled with ballast (such as sand or concrete - not included). The platform is supported by four rubber shock absorbing isolators. A flange is provided around the perimeter of the tray for mounting the isolated work surface.
- · Available in either type 304 stainless steel or powder coated steel.
- · Work surface not included.
- · Ships assembled.

Typical Inner Isolated 1" Thick Work Surface For 22" & 28" Deep Tables



- Work surface shown with 1" overhang on all sides for freestanding installations.
- · When in an elevation of casework, adjust overhang as needed.





QUALITY BY DESIGN

## STEEL TABLES

#### Construction Specifications For Steel: TAC, TAA, TAB, TCC, TCB, TCE Tables

Construction: All tables and sizes are supplied with lower "H" frames unless otherwise specified. All legs are 2" x 2", 16 gauge steel tubing. All lower frames are 1" x 2", 16 gauge steel tubing. All legs are bolted in place. Table legs are supplied with leveling bolts and PVC boots. Tables shipped unassembled.

Load Rating: All tables are supplied with a lower "H" or "U" frame, and will support a 600lb load evenly distributed. Tables supplied without a lower "H" or "U" frame can support a 600lb load if all legs are bolted securely to the floor. (ie: seismic design).

Apron: Standard apron height is 3-3/4" high. If HU option is added, apron is 3" high.

Drawers: Drawer is 15" wide unless otherwise specified.

Hanging Cabinets: 22" deep tables will only accommodate 18" deep hanging cabinets. 28" deep tables (will accommodate 18" or 22" deep hanging cabinets. All tables manufactured to accommodate hanging cabinets have a lower "U" frame (option code HU). All tables 72" and wider that are manufactured to accommodate hanging cabinets have heavy duty upper aprons.

#### WOOD TABLES

### Construction Specifications For Wood: TAC, TAA, TAB, TCC, TCB, TCE Tables

Construction: All tables and sizes are supplied with lower "H" frames unless otherwise specified. Frames are 3-3/4" high and 3/4" thick lumber. Legs are 2-1/8" X 2-1/8" solid lumber with 4" high shoes. Apron frames are bracketed and securely bolted together, legs are shipped unassembled (unless otherwise noted).

Load Rating: All tables are supplied with a lower "H" or "U" frame, and will support a 600lb load evenly distributed. Tables supplied without a lower "H" or "U" frame can support a 600lb load if all legs are bolted securely to the floor. (ie: seismic design).

Apron: Standard apron height is 3-3/4" high.

Drawers: Drawer is 15" wide unless otherwise specified.

Table Op	tions
06	One fixed shelf to create an "O" frame table (cannot be used with option HU - "U" frame table with floating rail)
17	Nylon levelers
48	Keyboard tray (replaces drawer)
49	Pin adjustable height stainless steel inserts, apply option code to sitting height tables. Legs are adjustable in 1" increments, from 28-3/4" high to 34-3/4" high (work surface not included).
87	Mobile table with locking swivel casters. Mobile tables of all sizes are supplied with a lower "H" frame, excluding mobile tables that accommodate hanging cabinets. A mobile table manufactured to accommodate hanging cabinets is specified with both options 87 and HU.
88	Mobile table with customer specified casters (provide complete specification and source for casters).
91	No lower frame (Tables may be supplied without a lower H or U frame if the table width is 48" or less, and/or the required load is 200lbs or less. All tables may be supplied without a lower "H" or "U" frame and support a 600lb load if all legs are bolted securely to the floor. (example: seismic design).
92	"U" frame style table with rear & side supports
93	Left side table legs only (no right side supports)
94	Right side table legs only (no left side supports)
95	Front table legs only (no back leg supports)
BA	Bolt adjustable height legs with stainless steel inserts
BAP	Bolt adjustable height legs with powder coated steel inserts
C33	Mobile table with 330lb leveling casters. Mobile tables of all sizes are supplied with a lower "H" frame, excluding mobile tables that accommodate hanging cabinets. A mobile table manufactured to accommodate hanging cabinets is specified with both options C33 and HU.
C66	Mobile table with 660lb leveling casters. Mobile tables of all sizes are supplied with a lower "H" frame, excluding mobile tables that accommodate hanging cabinets. A mobile table manufactured to accommodate hanging cabinets is specified with both options C66 and HU.
HU	"U" frame table with floating rail to hang cabinets on tables without drawers (TAC, TCC)
OL	Use when ordering a table with drawers to match cabinets with Architectual Overlay Design
WA	Welded table assembly
WF	Wood fronts - see specifications





QUALITY BY DESIGN

# **TABLE OPTIONS**

# Table Option Code Availability

		VELDED		STEEL	BOLTED TA	ABLES	WOOD BOLTED TABLES			MISCELLANEOUS TABLES			
Option Code	STA	TDC	TDA	TAC & TCC	TAA,TCB & TCE	TAB	TAC & TCC	TAA,TCB & TCE	ТАВ	ACT	ACC	SCT	ТАН
06	Std	•	•	•	•	•	•	•	•	-	•	-	-
17	-	•	•	•	•	•	•	•	•	•	•	•	•
48	-	•	•	ı	•	•	1	•	•	•	•	•	•
49	-	•	Std	•	•	•	•	•	•	ı	ı	ı	Std
87	•	•	•	•	•	•	•	•	•	•	ı	•	ı
88	•	•	•	•	•	•	•	•	•	•	•	•	-
91	-	-	1	•	•	•	•	•	•	ı	ı	ı	•
92	-	-	Std	•	•	•	•	•	•	-	Std	-	•
93	-	-	-	•	•	•	•	•	•	-	-	-	-
94	-	-	-	•	•	•	•	•	•	-	-	-	-
95	-	-	-	•	•	•	•	•	•	-	-	-	-
ВА	-	•	•	•	•	•	•	•	•	-	-	-	•
ВАР	-	•	•	•	•	•	•	•	•	-	-	-	•
C33	•	•	•	•	•	•	•	•	•	-	-	-	-
C66	•	•	•	•	•	•	•	•	•	-	-	-	-
HU	-	•	Std	•	-	-	-	-	1	-	Std	-	-
OL	-	-	-	-	•	•	-	-	1	-	-	-	-
OLP	-	-	-	1	-	-	•	•	•	-	-	1	-
WA	-	Std	Std	•	•	•	-	-	-	-	Std	-	-
WF	-	-	-	-	•	•	-	-	-	-	-	-	Std

Std Option is standard for this item (option code not required)

- Valid option for this item
- Not a valid option for this item