



IN-STOCK PRODUCTS SHIP IN **5-7** BUSINESS DAYS!



**RAPID SHIP PROGRAM**

1.20.2021

# THE RIGHT PRODUCT, AT THE RIGHT TIME, IN THE RIGHT WAY.

For 30 years New England Lab has built a solid reputation in the lab furniture industry by understanding client needs, providing quality products that meet those needs, and by our commitment to the highest level of service. It has long been our mission to partner with clients to deliver high quality furniture systems that are backed by time-tested experience and knowledgeable service.

NEL Direct fulfills this mission by partnering with clients to provide a high level of service, great value and a response through in-stock products. Our top-quality products and services on short lead-time projects is our focus and what makes up NEL Direct. Our Rapid Ship division stocks a variety of the most common laboratory and industrial furniture products and accessories such as:

- Fixed & Mobile Tables
- Base & Wall Cabinets
- Fume Hoods & Chemical Storage Cabinets
- Shelving, Storage & Accessories
- Fixtures, Sinks & Accessories
- Work Surfaces
- Chairs, Stools & Accessories

This catalog represents our core product offerings. Unless otherwise noted, in-stock items are available to ship anywhere within the continental US within 5-7 business days. Out of stock product, fabrication, customization and installation services can be coordinated upon request and may require longer lead times. For friendly, quick and reliable assistance, please contact us by toll free phone or by email at your convenience. We appreciate the opportunity to serve you and to meet your immediate industrial and laboratory furniture needs.

 [NELdirect.com](https://NELdirect.com)

 [info@NELdirect.com](mailto:info@NELdirect.com)

 888.635.2949



Follow NEL Direct for information, coupons, and promotions!

Painted steel: Bright White and Warm Gray are standard.

The symbols below indicate if it is only available in one color.



## Table of Contents

Adaptable Tables, Overhead Strut Shelving & Electrical Strip Assembly . . . . .	3
Adaptable Table Accessories . . . . .	4-6
Overhead Slotted Shelving, Plumbing Kit , Fixtures and Electrical Strip Assemblies . . . . .	4
Keyboard Trays and Monitor Arms . . . . .	5
Task Lights, CPU Holder and Anti-Fatigue Mat. . . . .	6
<i>Novus</i> Office & Lab Attachments . . . . .	7
Painted Steel Cabinets . . . . .	8-10
Wall and Suspended Cabinets . . . . .	9
Base Cabinets . . . . .	10
Painted Steel Accessories . . . . .	11-12
Reagent Shelving System . . . . .	13
<i>Metro</i> Freestanding Shelving . . . . .	14
<i>Metro</i> Utility Carts . . . . .	15
<i>Metro</i> Cleanroom Accessories . . . . .	16
<i>Metro</i> Starsys . . . . .	17
Work Surfaces . . . . .	18-19
Sinks, Pegboards and Acrylic Splashguards . . . . .	20
Faucets & Eyewashes . . . . .	21
Valves, Fume Hood Plumbing & Electrical Pedestals . . . . .	22
Fume Hoods & Specialty Cabinets . . . . .	23-24
<i>Justrite</i> Safety Cabinets & Cylinder Straps . . . . .	25
<i>Biofit</i> Lab Chairs . . . . .	26-27

# Adaptable Tables



## 1 CAMBRIDGE SERIES TABLES

### tables

48" wide x 30" deep  
60" wide x 30" deep  
72" wide x 30" deep

- 1" black epoxy top included; 2" side/front overhangs, flush with the back of the table frame
- table leg opening (subtract 8.5" from top width)
- can accommodate lower shelf

## 2 CAMBRIDGE SHELVING KITS - STRUT

### overhead strut shelving kit

48" table shelving kit  
60" table shelving kit  
72" table kit shelving

#### shelving kit includes:

- (2) 11 ga. painted steel strut uprights
- (2) shelf support brackets
- (2) bookstop rails
- (2) black plastic laminate shelves
- (2) bookend brackets
- bolts and hardware
- please note: electrical strip sold separately

## 3 ELECTRICAL STRIP ASSEMBLIES - STRUT

### power strip and rail

48" electrical strip kit  
60" electrical strip kit  
72" electrical strip kit

- raceway with 15' grounded cord, on/off switch, and 15A 120V outlets mounted to a steel support rail
- 36" power strip for 48" tables; 12 outlets
- 48" power strip for 60" tables; 16 outlets
- 60" power strip for 72" tables; 20 outlets



### tables

construction: fully welded frame with stainless steel bolted leg inserts

adjustable with 1" work surface

- 25"h to 37"h on levelers
- 30"h to 42"h on casters

mobility: leveling feet and casters are included if desired and specified

upper flexibility: optional shelving system bolts to rear table legs (adding 1.625" d)

lower flexibility: hanging rails support under work surface components (see pg. 9 & 10)

weight capacity: 1,000 lb. evenly distributed on frame (please account for top, storage & bench top equipment)

frame color: bright white or warm gray

### strut shelving kits

adjustment: brackets are adjustable in height along the strut (typically rising 47" above the top)

shelving: 1" black plastic laminate banded with a durable 3mm black PVC edge

\*phenolic shelving available upon request (see pg. 14)

flexibility: add/remove/modify kit on any standard Cambridge Series base table

weight capacity: supports 200 lb. evenly distributed per shelf

steel frame components: bright white or warm gray

shelving: black or gray

## CAMBRIDGE SHELVEING KIT - SLOTTED SINGLE



### single bay overhead slotted shelving

- 48" table shelving kit
- 60" table shelving kit
- 72" table shelving kit

#### shelving kit includes:

- (1) left slotted upright with service holes
- (1) right slotted upright
- (1) cross brace
- (2) painted steel shelves w/rear lip
- (4) tapered shelf brackets adjustable in 1" increments
- color: bright white only

BW

## SERVICE VALVES



### needle valve (left)

- VAC (yellow) - 61997762028
- AIR (orange) - 61997882021
- NIT (brown) - 61997812023

### ADA ball valve (right)

- VAC (yellow) - 61997782028
- AIR (orange) - 61997872021
- NIT (brown) - 61997822023

BW

## POST PLUMBING KIT



### plumbing kit

54" post plumbing kit

#### plumbing kit includes:

- (3) color-coded quick release plugs at top of hose
- soft PEX braided stainless steel hoses for AIR/NIT with color coded PVC labels
- Teflon braided stainless steel hose for VAC with color coded PVC label
- (3) bright white blind caps

## QUICK CONNECTS & HOSES



### quick connects (left)

- VAC (yellow) - 25980222028
- AIR (orange) - 25980222021
- NIT (brown) - 25980222023

### white hoses (right)

- VAC (yellow) - 25980402028
- AIR (orange) - 25980402021
- NIT (brown) - 25980402023

## ELECTRICAL STRIP ASSEMBLIES - SLOTTED



### economy

- 48" electrical strip kit
- 60" electrical strip kit
- 72" electrical strip kit

### standard

- 48" electrical strip kit
- 60" electrical strip kit
- 72" electrical strip kit

### premium

- 48" electrical strip kit
- 60" electrical strip kit
- 72" electrical strip kit

- twist lock plug on a 10' white cord and 90° cord grip
- raceway can be flipped so cord can be used either side of bench
- anodized aluminum with removable cover
- economy: (5) round standard 20A duplex outlets
- standard: (5) rectangular designer 20A duplex outlets, (2) type B USB ports
- premium: (6-8) rectangular designer 20A duplex outlets, (2) type B USB ports
- color: bright white only

BW



## MONITOR ARM



### monitor arm

IN-7000-FM

- supplied with mounting hardware for 6 different mounting methods
- color: silver, additional colors available



FLAT WHITE  
248



SILVER  
124



VISTA BLACK  
104



desk edge  
mount



through-hole  
mount



wall mount



reverse wall/table  
upright mount



side bolt  
mount



grommet hole  
mount



### monitor arm

IN-9112-S-FM

## CONFORM MONITOR ARM



### single monitor arm

WR-1SDA-CCG



### dual monitor arms

WR-2SDA-TPCCG

- single arm supports 1 computer monitor
- single arm maximum monitor height: 16"
- dual arm supports 2 computer monitors
- dual arm maximum monitor height: 19.5"
- color: silver
- maintenance free gas spring
- supports 5-17 lb. monitors
- integrated wire managers
- ability to fold down
- articulation range: 13"
- tilt range: -45° +90°
- clamp base

## KEYBOARD TRAY



### articulating slide-out tray

KT12-27

- size: 27"w
- 12.5" height adjustment range (7" up, 5.5" down)
- 23" track included
- lift to desired position and release

## KEYBOARD & MOUSE TRAY



### keyboard tray w/swivel mouse tray

KT12-19

- size: 19"w
- 12.5" height adjustment range (7" up, 5.5" down)
- 23" track included
- lift to desired position and release



## TASK LIGHT



### task light

- 12-5/16" wide light, 26 LEDs
- 21-5/16" wide light, 45 LEDs
- 22-9/16" wide light, 51 LEDs
- 34-3/8" wide light, 76 LEDs
- 46-3/16" wide light, 100 LEDs
- 58" wide light, 126 LEDs

- color: white
- screw mounting clips, in-line on/off rocker switch and power cord included
- 120 volts
- 4000K standard light temperature
- high efficiency with 87 Lm/W
- accessories sold separately

### accessories

- 2) connection cord
- 3) direct connector
- 4) magnetic mounting clips



## CPU HOLDER SUSPENDED



### cpu holder

8-1/4" wide - CPU29157

- color: black
- adjustable from 8-1/4"w - 3-3/4"w and 20-1/2"h - 12"h

## ANTI-FATIGUE MAT



### floor mat

WR-AFM-2918

- color: black
- 29.5" w x 18" d x 3/4" h
- 100% polyurethane foam with puncture resistant surface
- patent pending foot hold for convenient repositioning
- 18" beveled edges



## NOVUS TOOLBAR



table size	width	surface attachment
4'	40"	clamp mount*
5'	50"	clamp mount*
6'	63"	clamp mount*

- flexible organizer for your desktop with a variety of accessories to support your workspace
- (1) aluminum slatwall element with two slots for attaching accessories, monitor arms and task lights
- (2) aluminum posts with clamp mount



\*available with cable port mount

## NOVUS UPRIGHT BAR KIT




table size	width	attachment
4'	40.12"	mounting brackets
5'	52.13"	mounting brackets
6'	64.13"	mounting brackets

- (1) extruded aluminum slat rail bar with (2) mounting brackets and (2) end caps
- flush mount: attach bar to the back of the brackets - end caps not needed
- forward mount: attach bar to the face of the bracket and cap the ends

**\*For use with the Cambridge Table slotted upright system. Uprights not included.**

## ACCESSORIES



**my arm monitor arm**  
NV-MA-CM



**LifTEC arm III**  
NV-LT-3



**slatwall monitor arm**  
NV-CLII-209



**multi storage board**  
NV-MSB-99



**cell phone holder**  
NV-PHN-79



**tablet holder**  
NV-TH-89



**magnetic strip**  
NV-MS-109



**pen holder**  
NV-PH-69



**memo holder**  
NV-MB-39



**pura-line pen cup**  
NV-PBH-69



**penda small multi-purpose box**  
NV-SB-49



**shelf**  
NV-SWSHV-600 23.62"w x 12"d  
NV-SWSHV-600 31.5" w x 12"d  
NV-SWSHV-600 39.37"w x 12"d



# Painted Steel Cabinets



## 1 3-HIGH DRAWER SUSPENDED

### full width drawers

15" wide - 1950044

18" wide - 1150044

24" wide - 1250044

- may interfere with caster swivel at lower table height adjustments

## 2 HINGED GLASS WALL CABINETS

### double door

30" wide - 5310030

36" wide - 5410030

- 1/4" clear float glass
- (2) adjustable steel shelves included
- mounting channel included

## 3 BASE DOOR/DRAWER CABINETS

### double door

30" wide - 1310022

36" wide - 1410022

48" wide - 1510022

- (1) adjustable steel shelf included
- standing height (34-3/4"h)

### suspended cabinets

size: cabinets are 24"h and 22"d

construction: inset steel

drawers slides: full extension 100 lb. soft close slides

hardware: aluminum wire pulls and stainless steel 5-knuckle hinges

finished back and tops

color: bright white or warm gray

### wall cabinets

size: cabinets are 30"h and 14"d

construction: inset steel

hardware: aluminum wire pulls and stainless steel 5-knuckle hinges

color: bright white or warm gray



## DOOR/DRAWER SUSPENDED



### left hinged (shown)

18" wide - 1150222

24" wide - 1240222

### right hinged

18" wide - 1150022

24" wide - 1250022

- may interfere with caster swivel at lower table height adjustments

## 3-HIGH DRAWER SUSPENDED



### full width drawers

15" wide - 1950044

18" wide - 1150044

24" wide - 1250044

- may interfere with caster swivel at lower table height adjustments

## HINGED WALL CABINETS



### steel double door

30" wide - 5310060

36" wide - 5410060



### glass double door

30" wide - 5310030

36" wide - 5410030

- 1/4" clear float glass (glass wall cabinets only)
- (2) adjustable steel shelves included

## DETERMINING DIMENSIONS



### wall and suspended cabinets

size:

wall cabinets: 30"h x 14"d

suspended cabinets: 24"h x 22"d

construction: inset steel

hardware: aluminum wire pulls and stainless steel 5-knuckle hinges

color: bright white or warm gray

suspended cabinets:

drawer slides: full extension 100 lb. softclose slides

hanging (suspended file cabinets): files hang front to back in the drawer

mounting channels included on wall shelves

## SINK CABINETS



### double door sink cabinet

36" wide - 1418022  
48" wide - 1518022



### end double door sink cabinet

58" wide - 9900022

- sink supports available for use with undermount sinks
- powdercoat galvanized steel on cabinet bottom

## DOOR/DRAWER CABINETS



up to 24" wide



30" wide

### left hinged (shown)

18" wide - 1110222  
24" wide - 1210222

### right hinged

18" wide - 1110022  
24" wide - 1210022

### double door

30" wide - 1310022  
36" wide - 1410022  
48" wide - 1510022

- right hinged door/drawer is reverse of what is shown

## FULL DOOR CABINETS



### double door

36" wide - 1410011

- (1) adjustable steel shelf included

## 3-HIGH DRAWER CABINETS



### full width drawers

18" wide - 1110090  
24" wide - 1210090

## 4-HIGH DRAWER CABINETS



### full width drawers

18" wide - 1110044  
24" wide - 1210044  
30" wide - 1310097

### base cabinets

size: 34-3/4" h x 22" d

construction: inset steel

drawers slides: full extension 100 lb. soft close slides


hardware: aluminum wire pulls and stainless steel 5-knuckle hinges

leveling method: adjustable leveling feet

color: bright white or warm gray



## LEFT FRONT FILLER PANELS



### filler 34.75" high (left scribe)

1" wide - FFL1001

4" wide - FFL1004

6" wide - FFL1006

### toe base corner filler

9900001

### filler panel

2" wide - FFC1002

6" wide - FFC1006

- toe base filler required for corners
- can be cut to meet wall conditions
- powder coated steel for inset cabinets
- color: bright white or warm gray

## RIGHT FRONT FILLER PANELS



### filler 34.75 high (right scribe)

1" wide - FFR1001

4" wide - FFR1004

6" wide - FFR1006

- can be cut to meet wall conditions
- powder coated steel for inset cabinets
- color: bright white or warm gray

## REAR FILLER PANELS



### filler 34.75" high (rear scribe)

1" wide - 24" deep tops - ECS1001

7" wide - 30" deep tops - ECS1007


11" wide - hood cabinets - ECS1011

### filler 34.75" high

14" wide - island ends - ECC1014

- rear filler can be used for right/left hand applications
- scribe not required at island/peninsula ends
- can be cut to meet wall conditions
- powder coated steel for inset cabinets
- color: bright white or warm gray

## WALL FILLER PANELS



### 30" high fillers

1" wide - WFS6301

4" wide - WFS6304

- for use with 14"d wall cabinets
- wall fillers can be used for right/left hand applications
- can be cut to meet wall conditions
- powder coated steel for inset cabinets
- color: bright white or warm gray

## KNEESPACE PANELS



### knee panel 34.75" high

30" wide - SPC1030

36" wide - SCP1036

- assembly includes single angles for attachment to adjacent cabinets
- upper panel is removable to allow access to the services
- lower panel stays fixed in order to apply the coved base
- overlapping lower and upper panel allows for adjustment on uneven floors
- powder coated steel for inset cabinets
- color: bright white or warm gray

## FRONT RAILS




### 2" high

30" wide - FRB0030

36" wide - FRB0036

- front rails can be used at kneespace locations
- powder coated steel for inset cabinets
- color: bright white or warm gray

## OVERHEAD CEILING PANEL



### service panel

12 services - OSP0002

- takes the place of a standard ceiling tile
- ability to mount/disconnect quick connect service fixtures, electrical and data outlets
- 6 service access holes and 6 electrical cutouts
- panel is compatible with most T grid acoustical suspended ceiling structures
- fixtures sold separately
- color: bright white only
- see page #22 for quick connects

BW

## WALL SHELVING UPRIGHTS & BOOKEND BRACKETS



### double slotted uprights

36" high - WPA0036

- 1-5/8" w x 13/16" d
- slot pattern suitable for bookend brackets below
- pilasters should be mounted 1/2" on center
- color: bright white or warm gray



### pair of brackets

12" deep - SBP0012

### inverted pair of brackets

12" deep - SBP1012

- pair of shelf brackets are 6" h
- color: bright white or warm gray

## WALL AND REAGENT SHELVING



### plastic laminate

27" long - PLM1227FS

30" long - PLM1230FS

33" long - PLM1233FS

36" long - PLM1236FS

- 12" deep x 1" thick shelving to span a maximum of 36"
- for wall and reagent shelving only
- finished edge on all sides
- color: black (other colors can be readily fabricated; please consult your representative for lead time)

## UNDER COUNTER SUPPORT BRACKET



### steel bracket

29" deep - CBS0001

- reversible to support 30" d or 24" d work surfaces
- legs are 22" by 28" d welded from 1" x 2" 16-gauge steel tube
- recommended at 36" maximum intervals for most work surfaces
- color: bright white or warm gray

## GABLE LEGS



### gable leg 34.75" high

29" deep - GLS1029

- supports work surfaces or aprons where base cabinets are not required
- complete with wall mounting channel
- 1.5" w
- color: bright white or warm gray



## REAGENT UPRIGHTS



### slotted post assembly

90" high - RIV0090

- slot pattern suitable for bookend brackets
- adjustable in height on 1" increments
- should be mounted 1/2" on center
- 1" w x 2" d; double-sided, double-slotted post with threaded bolt and nut at top
- adjustable shelving slots begin above the work surface at approximately 16" above bench height
- each post sold with base support

## REAGENT CROSSBARS



### crossbar tube

120" length - RIH0120

- 1" x 2" tube with no penetrations for posts
- field drill holes to locate post bolts
- crossbar comes with 2 plastic end caps
- tube insert for seaming lengths over 120" sold separately

### seam connector insert

insert - RIJ0000

- tube insert for seaming lengths over 120"



### reagent shelving

construction: painted steel  
double-sided, double-slotted post with threaded top-bolt, floor mounting gusset and crossbar

#### installation:

- 1) mount gusset to floor
- 2) adjust post to be plumbed and level
- 3) cut crossbar to length
- 4) drill holes in crossbar for attachment to threaded top-bolts
- 5) secure assembly to base cabinets below
- 6) if possible, secure ends to walls or pipe chases for extra support

color: bright white or warm gray

spacing: 27-1/2", 30-1/2", 33-1/2" or 36-1/2" on center for 27", 30", 33" and 36" shelves respectively

shelving: p-lam or phenolic shelving and brackets (see pg. 12)

## SUPER ERECTA



### 18" deep 4-shelf unit

36" wide - M-EZ1836NC-4  
48" wide - M-EZ1848NC-4  
60" wide - M-EZ1860NC-4

### 24" deep 4-shelf unit

36" wide - M-EZ2436NC-4  
48" wide - M-EZ2448NC-4  
60" wide - M-EZ2460NC-4

- includes 4 shelves and 4 stationary posts with cap and leveling bolt
- chrome frame, posts and shelves
- open wire shelf design minimizes dust accumulation and allows free circulation of air

### metro shelving

800 lb. capacity per shelf up to 48" wide

600 lb. capacity per shelf over 48" wide

2,000 lb. maximum capacity per unit

all units 74" tall

easy assembly

nsf listed



## METROMAX i POLYMER



### 18" deep 5-shelf unit

24" wide - M-5X317GX3  
30" wide - M-5X327GX3  
36" wide - M-5X337GX3  
42" wide - M-5X347GX3  
48" wide - M-5X357GX3  
60" wide - M-5X367GX3  
72" wide - M-5X377GX3

### 24" deep 5-shelf unit

36" wide - M-5X537GX3  
42" wide - M-5X547GX3  
48" wide - M-5X557GX3  
60" wide - M-5X567GX3  
72" wide - M-5X577GX3

- includes 5 shelves and 4 stationary posts with cap and leveling bolt
- polymer frame, posts and shelves
- easy-to-clean removable polymer shelf mats
- Microban protection built into shelf mats, frames and posts



\*MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban Products Company, Huntensville, NC

## SUPER ADJUSTABLE 2



### 18" deep 5-shelf unit

36" wide shelving unit  
48" wide shelving unit  
60" wide shelving unit

### 24" deep 5-shelf unit

48" wide shelving unit  
60" wide shelving unit  
72" wide shelving unit

- includes 5 shelves and 4 stationary posts with cap and leveling bolt
- open-wire design minimizes dust accumulation and allows free circulation of air
- unique corner release system that allows shelves to be adjusted without tools
- type 304 stainless steel wire shelves and posts



## METROMAX i CART



### 2-shelf unit

18" x 30" - M-MXUC1830G-25  
24" x 36" - M-MXUC2436G-25

### 3-shelf unit

18" x 30" - M-MXUC1830-G-35  
24" x 36" - M-MXUC2436-G-35

- casters: 5" 5PCX polyurethane with polymer horns and stainless steel axles
- polymer frame, posts and shelves
- easy-to-clean removable polymer shelf mats
- Microban protection built into shelf mats, frames and posts
- all units are 39"h
- 900 lb. capacity evenly distributed
- type 304 stainless steel handle



\*MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban Products Company, Huntensville, NC

## DEEP-LEDGE CART



### 2-shelf unit

18" x 30" - M-BC2030-2D  
24" x 36" - M-BC2636-2D

### 3-shelf unit

18" x 30" - M-BC2030-3D  
24" x 36" - M-BC2636-3D



gray



black



blue

- chemical resistant high density polyethylene
- 2-3/4" d ledge for containment
- easy to position center shelf option
- easy-to-clean and corrosion proof polymer shelves
- 150 lb. capacity per shelf; 2-shelf unit capacity is 300 lb. and 3-shelf unit capacity is 400 lb. evenly distributed
- colors: gray, black, and blue

## SP SERIES UTILITY CARTS



### 2-shelf unit (chrome)

36" wide x 18" deep - M-2SPN33DC  
36" wide x 24" deep - M-2SPN53DC

### 3-shelf unit (chrome)

18" x 30" - M-3SPN33DC  
24" x 36" - M-3SPN53DC

- casters: 5MP polyurethane with plated horns, axles and donut bumpers
- steel with chrome finish
- 900 lb. capacity per cart
- 39"h

### 2-shelf unit (stainless steel)

36" wide x 18" deep - M-2SPN33PS  
36" wide x 24" deep - M-2SPN53PS

### 3-shelf unit (stainless steel)

18" x 30" - M-3SPN33PS  
24" x 36" - M-3SPN53PS

- casters: 5PC polyurethane with plated horns, stainless steel axles and donut bumpers
- type 304 stainless steel
- 900 lb. capacity per cart
- 39"h



## STAINLESS STEEL TABLE



### 30" deep table

36" wide - M-CTP3036S  
48" wide - M-CTP3048S  
60" wide - M-CTP3060S  
72" wide - M-CTP3072S

- perforated work surface
- twist - height adjustable legs: 33"-40"
- non-conductive
- type 304 stainless steel
- bench top is 14 gauge
- 3/4" holes on 1" centers
- appropriate for use in FED. Std. 209E Class 1 environments

## GOWNING BENCH



### 16" deep bench

36" wide - M-GB1636S  
48" wide - M-GB1648S  
60" wide - M-GB1660S  
72" wide - M-GB1672S

- bench top is 14 gauge, type 304 stainless steel
- non-conductive
- stainless steel footplates allow bench to be free standing or mounted to floor
- 18" h

## GARMENT STORAGE RACK



### 24" deep storage rack

36" wide - M-GSR2436  
48" wide - M-GSR2448  
60" wide - M-GSR2460

- type 304 stainless steel
- non-conductive
- adjustable shelves and dividers
- 69" h
- stem casters with brakes: nickel horn, resilient tread wheel, dust cover and celcon bearing

## WIRE WALL SHELVING



\*double shelf with longer post shown; single is standard

### wire shelves

14" wide x 24" long - M-1424NS  
14" wide x 30" long - M-1430NS  
14" wide x 36" long - M-1436NS

### end shelf support

14" wide - M-1WS14S

### middle shelf support

14" wide - M-2WS14S

### uprights

13-7/8" high - M-13PDFS

- maximum unit capacity not to exceed 250 lb.
- end shelf mount is for the end of the run
- middle shelf support mount is for middle of a run
- post sizes is for 1 tier shelving units - multiple tier shelving is available for longer uprights\*
- stainless steel





## TALL CABINETS - MOBILE



HD1

### cabinets

M-SXRD76CM3

M-SXRD76CMHD1

- Microban Antimicrobial Protection coats the drawers and doors inhibiting growth of bacteria
- aluminum interior structure
- configurable interior space: 66" x 41-1/3"
- recommended load weight of 900 lb.
- 5" diameter casters- front 2 casters have color-matched toe-brakes
- 41-1/3"w x 72-1/2"h



\*MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban Products Company, Huntensville, NC

## MOBILE WORKCENTER



### single width workcenter 23.6"

M-SXRMWS36EOH3

### double width workcenter 43.4"

M-SXRMWD36EOH3

### triple width workcenter 63.2"

M-SXRMWT36EOH3

- Microban Antimicrobial Protection coats the drawers and doors which inhibiting growth of bacteria
- aluminum steel substructure with advanced polymer cover
- overhead cabinets easy-to-clean shelves available in both polymer and epoxy coated wire designs
- work surface heights available: 33", 36", 39", 42" and 45"
- heavy duty drawer options: single or double-wide modules
- work surfaces 29"d are available in laminate and epoxy
- 5" polyurethane plate casters, 2 with brakes



\*MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban Products Company, Huntensville, NC







## 1 SINGLE-MOTION EYEWASH

### **pull down**

EW849LH-L

EW849LH

- swinging head down to operational position activates water flow
- remains in operation until spray head is returned to storage position
- finish: forged brass with polished chrome plated finish

## 2 MIXING FAUCET

### **mixing faucet (with VB)**

L414-8VB-55

- mixing faucet: deck-mounted, with vacuum breaker for hot and cold water
- handles: forged brass four-arm handles with color-coded index discs
- finish: forged brass with polished chrome plated finish

## 3 GRAY EPOXY RESIN

### **work surfaces**

30" x 48" - EPX3048-GRY

30" x 60" - EPX3060-GRY

30" x 72" - EPX3072-GRY

### **sink top\***

30" x 50" - EPX3050E-GRY

### **backsplash**

4" x 60" - EPX0460-GRY

4" x 100" - EPX04100-GRY

### **sidesplash**

4" x 29" - EPX0429-GRY

### **faucet**

valve units: self-contained compression valve with replaceable stainless steel seats

gooseneck: 8" rigid/swing convertible goose-neck

inlet: 1-3/16" male shank with (2) 3/8" OD flexible copper tubes; furnished complete with locknut and washer

outlet: 3/8" NPS female outlet; aerator included

vacuum breaker (VB): integral vacuum breaker to prevent backflow; breaker has replaceable seat and ultra-light float cup to resist spilling at low flow

### **work surface**

1" thick monolithic epoxy resin

edges: 1/8" bevel with drip groove on underside

splash: applied

adhesive: two-part epoxy provided as needed

other sizes can be readily fabricated; please consult your representative for lead times

\*sinktop E: E indicates that the top includes a gray D55 drop-in epoxy sink (25"x15"x10"), cutout and outlet; sinks are centered right to left in the work surface

## BLACK EPOXY RESIN

**work surfaces**

30"x 48" - EPX3048  
 30"x 60" - EPX3060  
 30"x 72" - EPX3072  
 30"x 100" - EPX30100  
 36"x 100" - EPX36100

**sink top\***

30"x 50" - EPX3050E  
 30"x 60" - EPX3060E  
 30"x 72" - EPX3072E

**backsplash**

4"x 60" - EPX0460  
 4"x 100" - EPX04100

**sidesplash**

4"x 29" - EPX0429

- edges: 1/8" bevel, underside drip groove
- adhesive: two-part epoxy provided as needed

**work surfaces**

thickness: 1"

splash: applied

other sizes can be readily fabricated;  
 please consult your representative for  
 lead times

**E - epoxy sinks**  
**S - stainless sinks**

**\*sink tops**

sinktop E: E indicates that the top  
 includes a black d55 drop-in epoxy  
 sink (25"x15"x10"), cutout and outlet;  
 sinks are centered right to left in the  
 work surface

sinktop S: S indicates SLXD2225-A-  
 GR-JX  
 stainless steel drop-in sink  
 (22"x16"x12"),  
 cutout and strainer; sink ledge can  
 accommodate a quick-ship mixing  
 faucet and eyewash as well as single  
 faucet; left 2 holes come with caps;  
 sinks are centered right to left in the  
 work surface

**see page 18 for gray epoxy  
 resin work surfaces**

## BLACK PHENOLIC RESIN

**work surfaces**

30"x 48" - PHN3048  
 30"x 60" - PHN3060  
 30"x 72" - PHN3072  
 30"x 120" - PHN30120

**sink top\***

30"x 60" - PHN3060E  
 30"x 72" - PHN3072E  
 30"x 60" - PHN3060S

**backsplash**

4"x 120" - PHN04120

**sidesplash**

4"x 29" - PHN0429

- laminated kraft paper finished on all 4  
 edges and both faces
- edge: 1/8" bevel

## GRAY PHENOLIC RESIN

**work surfaces**

30"x 48" - PHN3048-GRY  
 30"x 60" - PHN3060-GRY  
 30"x 72" - PHN3072-GRY  
 30"x 120" - PHN30120-GRY

**sink top\***

30"x 60" - PHN3060E-GRY  
 30"x 72" - PHN3072E-GRY  
 30"x 60" - PHN3060S-GRY

**backsplash**

4"x 120" - PHN04120-GRY

**sidesplash**

4"x 29" - PHN0429-GRY

- laminated kraft paper finished on all 4  
 edges and both faces
- edge: 1/8" bevel
- please note: gray phenolic will have a  
 black edge

\*gray phenolic with gray core can be  
 ordered for an additional fee

## BLACK PLASTIC LAMINATE

**work surfaces**

30"x 48" - PLM3048  
 30"x 60" - PLM3060  
 30"x 72" - PLM3072  
 30"x 120" - PLM30120

**backsplash**

4"x 120" - PLM04120

**sidesplash**

4"x 29" - PLM0429

- p-lam work surfaces: medium density  
 particleboard with 1/16" thick  
 laminate on both faces finished with a  
 durable 3mm PVC edge on all 4 edges
- edges: 1/8" radius
- splash: applied
- color: black (matching edgeband)
- standard grade


## GRAY PLASTIC LAMINATE

**work surfaces**

30"x 48" - PLM3048-GRY  
 30"x 60" - PLM3060-GRY  
 30"x 72" - PLM3072-GRY  
 30"x 120" - PLM30120-GRY

- p-lam work surfaces: medium density  
 particleboard with 1/16" thick  
 laminate on both faces finished with a  
 durable 3mm PVC edge on all 4 edges
- edges: 1/8" radius
- splash: applied
- color: gray (matching edgeband)
- standard grade

## STAINLESS PEGBOARDS



### size

24" wide x 30" high - 32 pegs - V2430

- material: 20 gauge, type 304 stainless steel, polished to #4 finish
- installation: wall mount bracket shipped with each pegboard
- 6" long 1/2" diameter white polypropylene pegs
- cleaning: safe to autoclave
- integrated drip tray

## EPOXY SINK



### sink

D55

- drop-in
- 25" w x 15" h x 10" d
- cutout and outlet
- colors: black and gray



### outlet

OUTL-S03R-001

### sink strainer

STRN-01-001

- for use with D55 sink
- colors: black and gray

## STAINLESS STEEL SINK



### sink

SLXD-2225

- 22" w x 16" h x 12" d
- cutout and strainer




### acrylic splashguard

30" x 12" x 0.5" - ASGN3012-SS29-SS8

30" x 18" x 0.75" - ASGN3018-SS29-SS14

- notched with stainless steel U-channel
- eased and flame-polished edges
- 2" radius upper corner

## EPOXY PEGBOARDS



### sizes

24" wide x 30" high - 39 pegs - EPB2430

30" wide x 30" high - 46 pegs - EPB3030

- material: 1" thick black (or gray) epoxy resin with beveled edges
- installation: 4 screw holes provided for wall attachment
- drip trough: 2" d stainless steel with 36" clear flexible drain tube
- some assembly required



## MIXING FAUCET



### mixing faucet (with VB)

1) L414-8VB

2) L424-8VB-55



### mixing faucet (no VB)

3) L424-8

4) L2224



\*serrated tip available  
-BO140S

### standard mixing faucet

mixing faucet: deck-mounted, with hot and cold water

valve units: self-contained compression valve with replaceable stainless steel seats

gooseneck: 8" rigid/swing convertible gooseneck

inlet: 1-3/16" male shank with (2) 3/8" OD flexible copper tubes; furnished complete with locknut and washer

outlet: 3/8" NPS female outlet; included ten serration hose end or aerator

vacuum breaker (VB): integral vacuum breaker to prevent backflow; breaker has replaceable seat and ultra-light float cup to resist spilling at low flow (#1 & #2 only)

finish: forged brass with polished chrome plated finish

handles (BH): 4" forged brass wrist blade handles with color-coded index discs

## PURE WATER FAUCET



### pure water faucet

L7833SC

### standard pure water faucet

pure water faucet: deck mounted; for distilled, de-ionized or reverse osmosis water

interior lining: inert polypropylene; pure water comes in contact only with inert plastic

valve units: diaphragm-type valve; brass valve stem and bonnet with inert elastomer diaphragm; valve has manual on/off switch

handles: black nylon knurled handle with color-coded index discs

riser: 6" rigid brass riser

inlet: 3/8" IPS male shank with 3/8" OD tube connection, furnished complete with 3/8" OD compression adaptor for inlet

outlet: seven serration plastic hose end

finish: forged brass with polished chrome plated finish

## SINGLE MOTION EYEWASH & DRENCH HOSE



### pull down

EW849LH-L

EW849LH

- swinging head down to operational position activates water flow
- remains in operation until spray head is returned to storage position



### drench hose

EW1022

### eyewash and drench hose

spray head assembly: two GS-Plus™ spray heads with "flip top" dust covers and internal flow control

valve: 1/2" IPS plug-type valve with Teflon® coated O-ring seals

strainer: in-line strainer to protect valve and spray head from debris





supply: 1/2" NPT male inlet

sign: ANSI-compliant identification sign

finish: forged brass with polished chrome plated finish

## QUICK CONNECTS

services available:

	AIR - ORANGE
	NIT - BROWN
	VAC - YELLOW
	GAS - BLUE



### panel mount bodies

QCFL-B-3M-K8 - NIT  
QCFL-B-3M-K2 - AIR  
QCFL-B-3M-K4 - VAC  
QCFL-B-3M-K5 - GAS

## PVC HOSE



### white hose

HPV3-072-3F-6

### standard valves

valve unit: quarter-turn open/close with chrome plated brass ball and molded TFE seals

handle: chrome plated forged brass lever handle with color-coded index disc




inlet: furnished with 3/8" IPS mounting shank (assembled), locknut and washer, NPT male inlet

outlet: 3/8" NPT female outlet with removable ten serration hose end

finish: forged brass with polished chrome plated finish

## BALL VALVES

services available:

	AIR - ORANGE
	NIT - BROWN
	VAC - YELLOW



### wall mount

L4200-158WSA



### deck mount single

L4200-131WSA



### deck mount double

L4200-132WSA



### GAS - BLUE

### wall mount

L4160CV-158WSA

## ELECTRIC PEDESTAL BOX








### outlet fitting

E300WS - single gang, single face  
E400WS - single gang, double face  
E500WS - double gang, single face  
E600WS - double gang, double face

- complete with grounding screws, mounting shank and locknut
- wrinkle black powder coated finish
- \*electrical outlets and plate not included

## FUME HOOD PLUMBING

services available:

	AIR - ORANGE
	GAS - BLUE
	NIT - BROWN
	VAC - YELLOW
	CW - GREEN



### outlet fitting

L022-WSA

L022CV-WSA

- use with fume hood gas valves
- mounting: panel mounted flange with 45 degree angle hose end; furnished with mounting shank, locknut and washer; 3/8" NPT male inlet
- natural gas supplied with internal check valve (CV)
- brass outlet fittings with a powder coated finish to match service index button color



### rod-driven valve

(gasses) L3185N - "L" dimension 9.5"  
(water) L3185W - "L" dimension 30"

- angle pattern valve for installation within side wall of hood; inlet and outlet are 90°; 3/8" NPT female inlet and outlet
- valve type: needle valve for gasses and water valves as required
- valve body: forged brass
- fully assembled and factory tested prior to shipment
- can be plumbed up or down in field



### panel-mounted gooseneck

L074-WSA

- use with fume hood water valves
- backflow prevention: includes (L108) in-line vacuum breaker
- mounting: panel mounted turret with 6" rigid/swing gooseneck; furnished with mounting shank, locknut and washer; 3/8" NPT male inlet



# Fume Hoods



## 1 PRO SERIES FUME HOODS

### 5' hood

60" wide - 7321040

- 12" diameter duct collar
- 80 ft/min at 18" open has 533 CFM at 0.05 wg
- 100 ft/min at 18" open has 667 CFM at 0.07 wg

### 6' hood

72" wide - 7421040

- 12" diameter duct collar
- 80 ft/min at 18" open has 660 CFM at 0.07 wg
- 100 ft/min at 18" open has 825 CFM at 0.11 wg

### double door

30" wide - 1331011

36" wide - 1431011

- vent kit included
- molded polyethylene tub liner cabinet insert
- polyethylene lined back door includes plastic roller catch
- 34.75"h x 18"d, suitable for use with hood cupsink
- 3/4" black phenolic adjustable shelf
- 5-knuckle stainless steel hinges
- aluminum wire pulls
- color: bright white or warm gray with red lettering "ACID"

### fume hoods

bypass: automatically compensating bypass for CAV and field convertible restrictor panel for VAV operation

liner: FRP fiberglass reinforced polyester

sash: chain and sprocket vertical rising with sash stops at 18" open

electrical: 2 GFCI 120V 20A duplex outlets, light fixture and switch

light: UL/CSA approved LED bulbs

alarm: TEL AFA1000 air flow sensor with audible and visual alarm and digital readout plugs into roof mounted duplex outlet

plumbing: pre-punched for future fixtures (sold separately; interior and exterior access panels)

### fume hoods cont...

work surface: 1-1/4" dished black epoxy with right side cupsink and cover

airfoil: type 316 stainless steel with cord notches

duct collar: type 316 stainless bell mouth shape

color: bright white or warm gray

size requirements:  
32-5/8" deep - meant to sit on a 30" deep bench

54-1/4" high - sash rises an additional 7-1/2" above hood for a total of 96-3/4" above the floor on the bench height cabinets



## INSULATED SOLVENT STORAGE CABINETS



### double door

30" wide - 1332011

36" wide - 1432011

- UL 1275 listed
- built to NFPA 30, NFPA 45 and OSHA standards
- painted galvanized steel adjustable shelf
- painted steel piano hinge
- three-point lockable self-latching handle
- insulated 2" construction



## ACID STORAGE CABINETS



### double door

30" wide - 1331011

36" wide - 1431011

- vent kit included
- molded polyethylene tub liner cabinet insert
- polyethylene lined back door includes plastic roller catch
- 3/4" black phenolic adjustable shelf
- 5-knuckle stainless steel hinges
- aluminum wire pulls

### specialty cabinets

size: 34.75"h x 18"d

suitable for use with cupsink

color: bright white or warm gray

## ACID CABINET VENT KIT



### vent kit

AC-VENTKIT

kit includes parts needed to connect a vented acid cabinet to a fume hood (or other exhaust source)

- 8" PVC encase venting hose (longer than shown in image)
- (2) 90 degree PVC threaded elbows
- (1) 1-1/4" threaded adapter flange
- (4) heavy-duty zip clips

\* included with purchase of each acid cabinet, and can also be sold separately.

## WALL MOUNT SAFETY CABINETS



### manual close

43"W x 24"H (17 gallon) - JRIS-8917008  
43"W x 44"H (20 gallon) - JRIS-893400



## STANDING SAFETY CABINETS



### manual close

43"W x 44"H (30 gallon) - JRIS-893000  
43"W x 65"H (45 gallon) - JRIS-894500  
34"W x 65"H (60 gallon) - JRIS-896000

### self close

43"W x 44"H (30 gallon) - JRIS893020  
43"W x 65"H (45 gallon) - JRIS-845020  
34"W x 65"H (60 gallon) - JRIS-896020



## COUNTERTOP SAFETY CABINET



### manual close

17"W x 22"H (4 gallon) - JRIS-890405  
23.25"W x 35"H (12 gallon) - JRIS-891205  
23.25"W x 44"H (15 gallon) - JRIS-891505

### self close

17"W x 22"H (4 gallon) - JRIS-890425  
23.25"W x 35"H (12 gallon) - JRIS891225  
23.25"W x 44"H (15 gallon) - JRIS891525



## CYLINDER LOCKERS



### lockers

10-cylinder vertical (30"W) - JRIS-23006  
20-cylinder vertical (60"W) - JRIS-23007

- slanted roof panel towards back
- 100% welded aluminum
- NFPA and OSHA compliant
- heavier gauge aluminum mesh and extruded frame
- size: 65"h x 32"d

## CYLINDER STRAPS



### wall strap

8.125"W x 4.625"H x 1.875"D - TMR-970037

- cast iron aluminum
- wall mounting: screw holes at each side
- 1" w x 54"L black nylon strap with nickel-plated, non-slip spring catch and buckle
- holds cylinders 4" to 14" in diameter
- one cylinder per wall strap



### bench clamp

6"W x 4.5"H x 3-1/4"D- TMR-970035

- 2 screw clamps to tighten for extra firm mounting
- rugged cast aluminum bench clamp
- 1"W x 54"L nylon strap with nickel-plated, non-slip spring catch buckle

### standard safety cabinets

designed to meet OSHA and NFPA standards

18-gauge thick double wall, welded steel with 1-1/2" of insulating air space

three-point stainless steel bullet self-latching system

galvanized 30 lb. capacity steel shelves designed to direct spills to back and bottom

shelves adjust on 3" centers

dual vents with flame arresters

four adjustable self-leveling feet

grounding connector

manual-close doors open to full 180° and self latch when closed

self-close doors shut and latch when fusible link melts at 165° Fahrenheit



## BRIDGEPORT



**lab chair**  
BTS-M-RC

- backrest: 14.5" w x 9.5" h
- seat: concave, 18.5" w x 16.5" d with internal seatboard bumperguard
- base S: 5-legged tubular steel with 21" d attached footring, 23" leg spread
- adjustment: 21" to 28" seat height

## BRIDGEPORT II



**lab chair**  
BTA-M-RC-ATF

- backrest: 14.5" w x 9.5" h
- seat: concave, 18.5" w x 16.5" d with internal seatboard bumperguard
- base A-ATF: 5-legged cast aluminum with 20" d adjustable black and chrome footring; 25.6" leg spread
- adjustment: 19" to 26" seat height

## UNIQUEU



**lab chair**  
UUS-M-RC

- backrest: 16.5" w x 12.5" h with 0.09375" ventilating ribs, self-skinned urethane
- seat: self-skinned urethane, 18.5" w x 17" d x 1" t with waterfall front, shaped rear edge and ventilating ribs
- base S: 5-legged tubular steel with 21" d attached footring, 23" leg spread
- adjustment: 20" to 27" seat height
- please note: available in black only

### standard biofit chairs

controls: task control - soft touch  
pneumatic seat-height adjustment,  
fixed rearward seat tilt of 3.5 degrees,  
backrest tilt and backrest height adjustment

warranty: 13 years against defects in  
workmanship or abnormal wear for  
24/7 usage

pneumatic cylinders are covered for the  
functional lifetime of the chair

assembly: some is required

backrest provides lumbar support

casters: RC standard safety casters  
(dual wheel casters that resist  
movement when seat is not occupied)

## COLOR SELECTIONS\*



charcoal  
(P28605)

royal blue  
(P28542)

black  
(P28540)

\*vinyl upholstery only



- add arms to any chair (PSAS)  
(not available in UniqueU models)

## UNIQUEU II



**lab chair**  
UUA-M-RC-ATF

- backrest: 16.5" w x 12.5" h with 0.09375" ventilating ribs, self-skinned urethane
- seat: self-skinned urethane, 18.5" w x 17" d x 1" t with waterfall front, shaped rear edge and ventilating ribs
- base A-ATF: 5-legged cast aluminum with 20" d adjustable black and chrome footring; 25.6" leg spread
- adjustment: 18" to 25" seat height
- please note: available in black only



## REGENT



### lab chair

RTS-M-RC

- backrest: 14.5" w x 9.5" h
- base S: 5-legged tubular steel with 21" d attached footring, 23" leg spread
- adjustment: 19" to 26" seat height

## REGENT II



### lab chair

RTA-M-RC-ATF

- backrest: 14.5" w x 9.5" h
- base A-ATF: 5-legged cast aluminum with 20" d adjustable black and chrome footring; 25.6" leg spread
- adjustment: 19" to 26" seat height

## FOOTRESTS



### footrest

20"W x 11"D - FS-1

12"W x 11"D - FS-2

- height: adjustable height ranges from 3" to 11" in 1" increments
- metal parts: black powder coated finish
- slope: 10 inches

## REXFORD



### stool

RX-M-RC

- base S: 5-legged tubular steel with 21" d attached footring, 23" leg spread
- adjustment: 20" to 27" seat height

## REXFORD II



### stool

RXA-M-RC-ATF

- base A-ATF: 5-legged cast aluminum with 20" d adjustable black and chrome footring; 25.6" leg spread
- adjustment: 18" to 25" seat height

### standard biofit chairs

controls: task control - soft touch  
pneumatic seat-height adjustment,  
fixed rearward seat tilt of 3.5 degrees,  
backrest tilt and backrest height adjustment

warranty: 13 years against defects in  
workmanship or abnormal wear for  
24/7 usage

pneumatic cylinders are covered for the  
functional lifetime of the chair

assembly: some is required

backrests: 14.5" w x 9.5" h and include  
lumbar support

seat: round, 16" d, upholstered with  
3-1/2" of resilient molded foam  
cushioning, internal seatboard  
bumperguard

casters: RC standard safety casters  
(dual wheel casters that resist  
movement when seat is not occupied)





# How do we support you?



Foster relationships through responsive support & dependable communication



Design assistance using Sketchup helping you envision your new space




Provide adaptable tested solutions that support current & future innovation



Efficiently and rapidly fulfill orders according to your needs


PROJECT NAME: \_\_\_\_\_

Design Layout



PROJECT NAME: \_\_\_\_\_

Design Layout



PROJECT NAME: \_\_\_\_\_

## Design Layout

