

EW1020

Drench Hose Unit, Deck Mounted



Application: Drench hose unit for deck mounting. *Note: Under ANSI Z358.1-2014, drench hose units supplement, but do not replace, other types of emergency equipment.*

Mounting: Deck flange has handle locator guide to position handle facing forward at all times.

Spray Head: Single FS-Plus™ spray head. Spray head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Valve: Forged brass squeeze valve activated by stainless steel lever handle. Valve has replaceable stainless steel seat for exceptional durability.

Hose: 8' reinforced PVC hose. 300 PSI maximum working pressure. *Note: Hose must be inspected at least monthly for indications of wear, abrasion, loss of flexibility or loosening of end connections.*

Supply: 3/8" NPT male swivel inlet.

Sign: Furnished with universal identification sign.

Quality Assurance: Unit is fully assembled and water tested prior to shipment. Unit is third party certified to comply with ANSI Z358.1 - 2014.

Additional Model

EW1020BP Same as above except with in-line dual check backflow preventer for installation on inlet of hose. Backflow preventer is certified to comply with ASSE 1024/CSA-B64. *Note: Check with code authority for compliance with local plumbing code.*

EW1025

Drench Hose Unit, Wall Mounted



Application: Drench hose unit for wall mounting. *Note: Under ANSI Z358.1-2014, drench hose units supplement, but do not replace, other types of emergency equipment.*

Mounting: Wall mounted hook holds unit on wall.

Spray Head: Single FS-Plus™ spray head. Spray head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Valve: Forged brass squeeze valve activated by stainless steel lever handle. Valve has replaceable stainless steel seat for exceptional durability.

Hose: 8' reinforced PVC hose. 300 PSI maximum working pressure. *Note: Hose must be inspected at least monthly for indications of wear, abrasion, loss of flexibility or loosening of end connections.*

Supply: 3/8" NPT male swivel inlet.

Sign: Furnished with universal identification sign.

Quality Assurance: Unit is fully assembled and water tested prior to shipment. Unit is third party certified to comply with ANSI Z358.1 - 2014.

Additional Model

EW1025BP Same as above except with in-line dual check backflow preventer for installation on inlet of hose. Backflow preventer is certified to comply with ASSE 1024/CSA-B64. *Note: Check with code authority for compliance with local plumbing code.*

Optional Features:

- Stainless steel dust cover for spray head (add suffix “DC”)
- Flexible stainless steel hose in place of PVC hose (add suffix “FSH”)
- Undercounter hose guide bracket to prevent hose from tangling or binding (add suffix “HG”)
- In-line vacuum breaker installed between valve and spray head assembly (add suffix “VB”)

Finish Options:

- Polished chrome plated finish with clear epoxy coating (PCL)
- Satin chrome plated finish with clear epoxy coating (SCC)
- Satin nickel plated finish with clear epoxy coating (SNC)

Accessories:

- AP3600 thermostatic mixing valve blends hot and cold water to deliver tepid water as provided by ANSI Z358.1-2014 (add suffix “TMV”). Refer to “Tempering Valves” section for complete technical information.